



Certificate number: 2011746

Date issued 16th November 2020

Date expired 15th November 2025 Original/Amendment *Original*

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Manufacturer: Socla SAS.

Factor: Watts Industries UK Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification, which is managed in accordance with ISO/IEC 17065.

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

390177301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Watts Industries UK Ltd
Colmworth Business Park
Eaton Socon
St Neots
PE19 8YX



UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2011746

The following products are covered by this certificate -

PRODUCT DESCRIPTION: Type TK Model IN, spring loaded resilient trim in line check valve cartridges with a plastic body, polymer guide and stem and EPDM `O` ring and seals. For insertion into pipes or fittings with specifically dimensioned bores. ATS3 – Without Production Surveillance.
MODEL(S): IN015; IN020; IN025; IN032; IN040; IN050.
SIZE: DN15 to DN50.
SCOPE: Manufacturer recommended maximum working pressure 16 Bar & maximum operating temperature 85°C. Hygienic purposes: Non-metallic materials suitable for continuous use up to 85°C. Above ground use only.
MATERIALS: Non-Metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES: N/A.
MARKING: Size DN15 and DN50: DN, Watts logo (W) on guide. Size DN20,25, 32 & 40: DN Ocean on guide.
ADDITIONAL NOTES: Opacity. All water contact & exposed components satisfy opacity requirements.

Extra Notes: