



## Product certificate K26384/04

Issued 2018-03-01

Replaces K26384/03

Page 1 of 2

### Thermostatic Mixing Valves

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

### Watts Industries France

as specified in this product certificate and marked with the Kiwa<sup>®</sup>-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline **BRL-K610/04**: "Thermostatic mixing valves" dated 01-02-2012, as well as the requirements of

**EN 1111:2017**: "Sanitary tapware - Thermostatic mixing valves (PN 10)".

Luc Leroy  
Kiwa

288171015

*Publication of this certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

#### Kiwa Nederland B.V.

Sir Winston Churchillaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00

Fax +31 88 998 44 20

[info@kiwa.nl](mailto:info@kiwa.nl)

[www.kiwa.nl](http://www.kiwa.nl)

#### Company

Watts Industries France

100 route Nationale

80132 HAUTVILLERS-OUVILLE

France

Tel. +33 322 24 70 11

Fax +33 322 23 16 83

[www.wattsindustries.com](http://www.wattsindustries.com)

Certification process  
consists of initial and  
regular assessment of:

- quality system
- product



## Thermostatic Mixing Valves

---

### PRODUCT SPECIFICATIONS

The products mentioned below belong to this certificate.

#### Minimix

Code 2297320  $\frac{3}{8}$ , with threaded connections  
Code 2297321  $\frac{1}{2}$ , with threaded connections  
Code 2297323  $\frac{1}{2}$ , with 15 mm compression fittings

Code 2297320M2  $\frac{3}{8}$ , with threaded connections  
Code 2297321M2  $\frac{1}{2}$ , with threaded connections  
Code 2297323M2  $\frac{1}{2}$ , with 15 mm compression fittings

### REMARK

The above listed products were not yet assessed for compliance with all Hygienic Aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation on materials and chemicals in drinking water and warm tap water supply), implemented on 19 July 2011, as specified in clause 4.2.2.1 of the Kiwa Evaluation guideline BRL-K610/04.

### APPLICATION AND USE

The thermostatic mixers are designed for application within following limits of use:

- working pressure from 50 kPa up to 1000 kPa;
- water temperature of maximum 70°C.

The recommended limits for correct operation are:

- working pressure of 100 kPa up to 500 kPa;
- water temperature of maximum 65°C.

### MARKING

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark: on the body.

Compulsory specifications:

- name or mark of the manufacturer on the body;
- indication for temperature selection: on the control device;
- the acoustic group, if classified: on the body;
- the flow rate class: on the body.

Method of marking:

- non-erasable;
- visible after assembly.

### RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Watts Industries France
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.