



Certificate number: 2411722 (1)

Issued 20/11/2024  
Expires 20/11/2029

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)  
Model number(s) – see Appendix

### SOC LA SAS.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

**Certificate Issued to:**  
SOC LA SAS  
365 rue du lieutenant putier  
71530 Virey le grand  
France



KUKreg4

# Product Certificate

Appendix to Certificate number: 2411722

---

The following products belong to this certificate

<b>PRODUCT DESCRIPTION</b> Type TK model WM range of spring loaded resilient trim check valve with plastic body and EPDM 'O'-rings. For insertion into fittings with specifically sized bores. ATS3 – Without Production Surveillance.
<b>MODEL(S)</b> Model WM015 – Ref W149015600 or 149B043318 WM015 - DN 15 Model WM020 – Ref W140020600 or 149F043509 WM020 - DN 20 Model WM025 – Ref W140025600 or 149F043510 WM025 – DN 25
<b>SIZE:</b> See models.
<b>SCOPE:</b> Manufacturer recommended maximum working pressure 10.0 Bar & maximum operating temperature 65°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 65°C.
<b>MARKING</b> W logo, DN, flow arrow printed on body.
<b>MATERIALS</b> Non-metallic materials assessed (BS6920) to point of discharge.
<b>BACKFLOW PROTECTION NOTES</b> N/A.
<b>ADDITIONAL NOTES</b> All water contact & exposed components satisfy opacity requirements.

## Extra Notes